



PRODUCT SPECIFICATION

R32 Monobloc



HM051M U43
HM071M U43
HM091M U43



Features

- All-in-one outdoor unit
- SCOP up to 4.45 (Average climate / Low temp. application) : A+++
SCOP up to 3.12 (Average climate / Mid temp. application) : A+
- COP up to 4.50 (Outdoor air 7°C / Leaving water 35°C)
- 100% heating capacity at -7°C OAT (@ LWT 35°C)
- Wide operation range (ambient : -25 ~ 35°C / water side : 15 ~ 65°C)
- R32 refrigerant with reduced global warming potential (GWP)
- R1 compressor
- Black Fin heat exchanger
- LG ThinQ
- KEYMARK / EHPA (for Austria) / MCS / EUROVENT certification

* EHPA (for Germany and Switzerland) under renewal of valid date

Model Line-up

Capacity	Unit	Model Name		
		Capacity (kW)		
		5.5	7.0	9.0
1 Phase Model 220 – 240V, 1Ø, 50Hz	Monobloc Unit	HM051M U43	HM071M U43	HM091M U43

Seasonal Energy

Description	Unit	HM051M U43	HM071M U43	HM091M U43		
Space Heating (According to EN14825)	Average Climate Water Outlet 35°C	SCOP	-	4.45	4.45	4.45
		Seasonal Space Heating Efficiency (η _s)	%	175	175	175
		Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+++	A+++	A+++
	Average Climate Water Outlet 55°C	SCOP	-	3.12	3.12	3.12
	Seasonal Space Heating Efficiency (η _s)	%	122	122	122	
	Seasonal Space Heating Eff. Class (A+++ to D Scale)	-	A+	A+	A+	

Nominal Capacity and Nominal Power Input

Description		OAT ¹⁾ (DB)	LWT ²⁾ (DB)	Unit	HM051M U43	HM071M U43	HM091M U43
Nominal Capacity	Heating	7°C	35°C	kW	5.50	7.00	9.00
		2°C	35°C		5.50	5.50	5.50
	Cooling	35°C	18°C		3.30	4.20	5.40
		35°C	7°C		5.50	7.00	9.00
Nominal Power Input	Heating	7°C	35°C	kW	1.22	1.56	2.15
		2°C	35°C		2.04	2.04	2.04
	Cooling	35°C	18°C		0.94	1.20	1.54
		35°C	7°C		1.20	1.56	2.14
COP	Heating	7°C	35°C	W/W	4.50	4.50	4.18
		2°C	35°C		2.70	2.70	2.70
	Cooling	35°C	18°C		3.52	3.51	3.50
		35°C	7°C		4.60	4.50	4.20
EER				W/W	2.80	2.70	2.60

1) OAT : Outdoor Air Temperature
2) LWT : Leaving Water Temperature

Product Specification

Technical Specification			Unit	HM051M U43	HM071M U43	HM091M U43	
Water Side	Operation Range (leaving water temperature)	Heating	Min. - Max.	°C DB	15 ~ 65		
		Cooling			5 ~ 27 (16 ~ 27) ¹⁾		
		DHW			15 ~ 80 ²⁾		
	Piping Connections	Water Circuit	Inlet	Inch	Male PT 1" according to ISO 7-1 (tapered pipe threads)		
		Outlet	Inch	Male PT 1" according to ISO 7-1 (tapered pipe threads)			
	Rated Water Flow Rate at LWT 35°C			LPM	15.8	20.1	25.9
Refrigerant Side	Operation Range (outdoor temperature)	Heating	Min - Max	°C DB	-25 ~ 35		
		Cooling			5 ~ 48		
	Compressor	Quantity		EA	1		
		Type		-	Hermetic Sealed Scroll		
	Refrigerant	Type		-	R32		
		GWP (Global Warming Potential)		-	675		
Precharged Amount			g	1,400			
	t-CO2 eq		-	0.945			
Sound Power Level	Heating	Rated		dB(A)	60		
Sound Pressure Level (at 1m)	Heating	Rated		dB(A)	50		
Dimensions	Unit	W x H x D		mm	1,239 x 834 x 330		
Weight	Unit			kg	88.0		
Exterior	Color / RAL Code			-	Warm Gray / RAL 7044		
Power Supply	Voltage, Phase, Frequency			V, Ø, Hz	220-240, 1, 50		
	Rated Running Current	Heating		A	5.4	6.9	9.6
		Cooling		A	5.3	6.9	9.5
	Recommended Circuit Breaker			A		16	20
Wiring Connections	Power Supply Cable (included earth, H07RN-F)			mm ² x cores	4.0 x 3C		

1) When fan coil unit not used.
2) DHW 58-80°C Operating is available only when the booster heater is operating.

Note

- Due to our policy of innovation some specifications may be changed without notification.
- Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- Sound power level is measured on the rated condition in according with ISO 9614 standard. Sound pressure level is converted from sound power level based on tonality penalty of 0dB and installation in free-field. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is according to the EN12102-1 under conditions of the EN14825.
- Performances are accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions acc. ErP regulation.
 - Rated running current : Outdoor Temp. 7°C DB / 6°CWB, LWT 35°C
- This product contains Fluorinated greenhouse gases.

PRODUCT SPECIFICATION

Performance Table for Heating Operation

Maximum Heating Capacity (Including Defrost Effect)

HM051M U43

Outdoor Temperature	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
	TC	TC	TC	TC	TC	TC	TC	TC
-25°C DB	3.79	3.67	3.54	3.42	-	-	-	-
-20°C DB	4.22	4.09	3.96	3.83	3.70	-	-	-
-15°C DB	4.66	4.52	4.38	4.25	4.11	3.97	-	-
-7°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-4°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
-2°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
2°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
7°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
10°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
15°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
18°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
20°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
35°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50

HM071M U43

Outdoor Temperature	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
	TC	TC	TC	TC	TC	TC	TC	TC
-25°C DB	4.82	4.67	4.51	4.36	-	-	-	-
-20°C DB	5.38	5.21	5.05	4.88	4.72	-	-	-
-15°C DB	5.93	5.76	5.58	5.41	5.23	5.06	-	-
-7°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
-4°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
-2°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
2°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
7°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
10°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
15°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
18°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00

HM091M U43

Outdoor Temperature	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
	TC	TC	TC	TC	TC	TC	TC	TC
-25°C DB	6.20	6.00	5.80	5.60	-	-	-	-
-20°C DB	6.91	6.70	6.49	6.28	6.06	-	-	-
-15°C DB	7.63	7.40	7.18	6.95	6.73	6.50	-	-
-7°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
-4°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-2°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
2°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
7°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00

Note

1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C), LPM : Liters Per Minute (l/min), TC : Total Capacity (kW)
2. Direct interpolation is permissible. Do not extrapolate.
3. Measuring procedure follows EN-14511.
 - Rated values are based on standard conditions and it can be found on specifications.
 - Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
 - In accordance with the test standard (or nations), the rating will vary slightly.
4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum Cooling Capacity

HM051M U43

Outdoor Temperature	LWT 7°C	LWT 10°C	LWT 13°C	LWT 15°C	LWT 18°C	LWT 20°C	LWT 22°C
	TC	TC	TC	TC	TC	TC	TC
10°C DB	5.16	5.65	6.14	6.47	6.96	7.29	7.62
20°C DB	5.29	5.59	5.89	6.08	6.38	6.58	6.77
30°C DB	5.43	5.53	5.63	5.69	5.79	5.86	5.92
35°C DB	5.50	5.50	5.50	5.50	5.50	5.50	5.50
40°C DB	5.57	5.50	5.43	5.38	5.31	5.27	5.22
45°C DB	5.64	5.50	5.36	5.27	5.13	5.04	4.94

HM071M U43

Outdoor Temperature	LWT 7°C	LWT 10°C	LWT 13°C	LWT 15°C	LWT 18°C	LWT 20°C	LWT 22°C
	TC	TC	TC	TC	TC	TC	TC
10°C DB	6.56	7.19	7.82	8.24	8.86	9.28	9.70
20°C DB	6.74	7.11	7.49	7.74	8.12	8.37	8.62
30°C DB	6.91	7.04	7.16	7.25	7.37	7.46	7.54
35°C DB	7.00	7.00	7.00	7.00	7.00	7.00	7.00
40°C DB	7.09	7.00	6.91	6.85	6.76	6.70	6.65
45°C DB	7.18	7.00	6.82	6.70	6.53	6.41	6.29

HM091M U43

Outdoor Temperature	LWT 7°C	LWT 10°C	LWT 13°C	LWT 15°C	LWT 18°C	LWT 20°C	LWT 22°C
	TC	TC	TC	TC	TC	TC	TC
10°C DB	8.44	9.24	10.05	10.59	11.40	11.93	12.47
20°C DB	8.66	9.15	9.63	9.95	10.44	10.76	11.08
30°C DB	8.89	9.05	9.21	9.32	9.48	9.59	9.69
35°C DB	9.00	9.00	9.00	9.00	9.00	9.00	9.00
40°C DB	9.11	9.00	8.89	8.81	8.70	8.62	8.54
45°C DB	9.23	9.00	8.77	8.62	8.39	8.24	8.09

Note

1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C), LPM : Liters Per Minute (l/min), TC : Total Capacity (kW)
2. Direct interpolation is permissible. Do not extrapolate.
3. Measuring procedure follows EN-14511.
 - Rated values are based on standard conditions and it can be found on specifications.
 - Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
 - In accordance with the test standard (or nations), the rating will vary slightly.
4. The shaded areas are not guaranteed continuous operation.





PRODUCT SPECIFICATION

Drawings


Category	Unit	Model Name		
		Capacity (kW)		
		5.5	7.0	9.0
1 Phase Model 220 - 240V, 1Ø, 50Hz	Monobloc Unit	HM051M U43	HM071M U43	HM091M U43

HM051M U43
HM071M U43
HM091M U43


[Unit : mm]



[Unit : mm]



3D View



No.	Part Name	Description
1	Entering Water Pipe	Male PT 1" according to ISO 7-1 (tapered pipe threads)
2	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (tapered pipe threads)
3	Strainer	Filtering and stacking particles inside circulating water
4	Top Cover	-
5	Front Panel	-
6	Side Panel	-
7	Low Voltage	Communication cable hole
8	Unit Power	Power cable hole
9	Water Pump	GRUNDFOS UPM3K 20-75 CHBL
10	Plate Heat Exchanger	Heat exchange between refrigerant and water
11	Pressure Gauge	Indicates circulating water pressure
12	Safety Valve	Open at water pressure 3 bar
13	Indoor Control Box	Indoor PCB and terminal blocks
14	Outdoor Control Box	Outdoor PCB and terminal blocks